

## 6 × 24 ( JIS規格品 )



## 6 × 24 ( JIS規格品 )

構成	6 × (A + 9 + 15)
用途	船舶用、水産用、その他一般

ロープ径 (mm)	外層 素線径 (mm)	破断荷重				(参考) 概算 単位質量 (kg/m)
		普通より				
		めっき		裸・めっき		
		G種		A種		
		t f	k N	t f	k N	
(6)	0.34	1.67		1.81		0.120
8	0.44	2.99	29.3	3.22	31.6	0.212
9	0.50	3.78	37.1	4.07	39.9	0.269
10	0.56	4.67	45.8	5.03	49.3	0.332
11.2	0.62	5.86	57.4	6.31	61.8	0.416
(12)	0.67	6.72		7.24		0.478
12.5	0.70	7.30	71.5	7.85	77.0	0.519
14	0.79	9.15	89.7	9.85	96.6	0.651
16	0.89	12.0	117	12.9	126	0.850
18	1.00	15.1	148	16.3	160	1.08
20	1.10	18.7	183	20.1	197	1.33
(22)	1.22	22.5		24.3		1.61
22.4	1.24	23.4	230	25.2	247	1.67
(24)	1.33	26.9		29.0		1.91
25	1.39	29.2	286	31.4	308	2.08
(26)	1.45	31.4		33.9		2.24
28	1.56	36.6	359	39.4	387	2.60
30	1.65	42.0	412	45.2	444	2.99
31.5	1.75	46.3	454	49.9	489	3.29
(32)	1.80	47.5		51.4		3.40
33.5	1.86	52.4	514	56.4	553	3.73
(34)	1.90	53.6		58.0		3.84
35.5	1.97	58.8	577	63.4	621	4.18
(36)	2.02	60.1		65.1		4.30
37.5	2.08	65.7	644	70.7	693	4.67
(38)	2.12	67.0		72.5		4.79
40	2.20	74.7	732	80.4	789	5.31
(42)	2.36	81.8		88.6		5.86
42.5	2.40	84.3	827	90.8	890	6.00
(44)	2.43	89.8		97.2		6.43
45	2.51	94.5	927	102	998	6.72
(46)	2.58	98.2		106		7.03
47.5	2.62	105	1,030	113	1,110	7.49
(48)	2.72	107		116		7.65
50	2.78	117	1,140	126	1,230	8.30