

6 × 37 (JIS規格品)



6 × 37 (JIS規格品)

構成	6 × (1 + 6 + 12 + 18)
より方	普通ZまたはS
用途	船舶用、クレーン用、機械用、その他一般

ロープ径 (mm)	外層 素線径 (mm)	破 断 荷 重				(参 考) 概 算 単 位 質 量 (kg/m)
		普 通 よ り				
		めっき G種		裸・めっき A種		
		t f	k N	t f	k N	
(6)	0.29	1.80		1.95		0.129
6.3	0.30	2.00	19.6	2.15	21.1	0.143
8	0.38	3.22	31.6	3.47	34.0	0.230
9	0.43	4.08	40.0	4.39	43.0	0.291
10	0.48	5.03	49.4	5.42	53.1	0.359
11.2	0.53	6.31	61.9	6.79	66.6	0.451
(12)	0.57	7.25		7.80		0.517
12.5	0.60	7.86	77.1	8.46	83.0	0.561
14	0.67	9.86	96.7	10.6	104	0.704
16	0.76	12.9	126	13.9	136	0.920
18	0.86	16.3	160	17.5	172	1.16
20	0.95	20.1	197	21.7	212	1.44
(22)	1.03	24.2		26.2		1.74
22.4	1.06	25.3	248	27.2	266	1.80
(24)	1.14	29.0		31.2		2.07
25	1.19	31.5	308	33.8	332	2.25
(26)	1.22	33.7		36.6		2.43
28	1.33	39.5	387	42.5	416	2.82
30	1.41	45.3	444	48.7	478	3.23
31.5	1.50	49.9	490	53.7	527	3.57
(32)	1.52	51.1		55.4		3.68
33.5	1.58	56.5	554	60.8	596	4.03
(34)	1.60	57.7		62.5		4.15
35.5	1.68	63.4	622	68.3	669	4.53
(36)	1.70	64.7		70.1		4.65
37.5	1.78	70.8	694	76.2	747	5.05
(38)	1.80	72.1		78.1		5.18
40	1.88	80.5	790	86.7	850	5.75
(42)	2.00	88.0		95.4		6.33
42.5	2.03	90.9	892	97.8	959	6.49
(44)	2.06	96.6		105		6.95
45	2.14	102	1,000	110	1,080	7.28
(46)	2.18	106		114		7.60
47.5	2.24	114	1,110	122	1,200	8.11
(48)	2.27	115		125		8.27
50	2.37	126	1,230	135	1,330	8.98
53	2.51	141	1,390	152	1,490	10.1
56	2.66	158	1,550	170	1,670	11.3
60	2.86	181	1,780	195	1,910	12.9
63	3.00	200	1,960	215	2,110	14.3
65	3.10	211		229		15.2
70	3.34	245		265		17.6
75	3.55	283		305		20.2
80	3.80	322		346		22.9
85	4.05	364		391		26.0
90	4.30	408		438		29.0
95	4.53	454		489		32.4
100	4.73	503		541		35.8